

SAFETY DATA SHEET

SDS No: 00127
Version: V01

MATTE-FIL MATTE URETHANE CLEARCOAT – FAST DRY
PRODUCT CODE: MC-8100

Preparation Date: June 18, 2020

1. IDENTIFICATION

Product identifier

Product Name: MATTE-FIL MATTE URETHANE CLEARCOAT - FAST DRY

Other means of identification

Product Code(s): MC-8100

Product type: Liquid

Synonyms: None

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use: Coating. Paints. Painting-related materials.
For Professional and Industrial Use Only

Restricted Uses: No information available

**Manufacturer /
Supplier Identifier:** Durafil Auto Technologies Inc.
1360 Blundell Road,
Mississauga, ON L4Y 1M5 Canada
Telephone: 905-896-7171

Emergency Telephone Number: 905-896-7171 (Monday to Friday 8 am - 5 pm EST, Canada)

24 Hour Emergency Phone Number (CANUTEC): (613) 996-6666 or 1-888-226-8832

2. HAZARDS IDENTIFICATION

OSHA/HCS Status:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification of the substance or mixture

GHS Classification	Category
Flammable Liquids	2
Skin Irritation	2
Serious Eye Damage/Eye Irritation	2A
Skin Sensitization	1B
Carcinogenicity	2
Specific Target Organ Toxicity (Single Exposure) (Respiratory tract irritation)	3

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****GHS label elements****Hazard pictograms:****Signal Word: Danger****Hazard Statements:**

Highly flammable liquid and vapor
Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation
May cause drowsiness and dizziness
Suspected of causing cancer
May cause damage to organs through prolonged or repeated exposure:
(central nervous system (CNS), kidneys, liver, respiratory system, eyes, skin)

Precautionary Statements**Prevention:**

Obtain special instructions before use
Read label before use
Do not handle until all safety precautions have been read and understood
Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
Use only outdoors or in a well ventilated area.
Avoid breathing vapor
Use explosion-proof electrical, ventilating, lighting, and all material-handling equipment
Ground and bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharges
Do not breathe dust, fume, gas, mist, vapors, spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves, protective clothing, eye protection and face protection
Wear respiratory protection
If medical advice is needed, have product container or label at hand
Wash hands thoroughly after handling
Avoid release to the environment
Do not eat, drink or smoke when using product
Keep out of reach of children

Response:

IF exposed or concerned: Get medical attention.
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse.
If skin irritation or rash occurs: Get medical attention.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

Version: V01
 Preparation Date: June 18, 2020
 SDS No.: 00127

**MATTE-FILMATTE URETHANE
 CLEARCOAT - FAST DRY
 PRODUCT CODE: MC-8100**

Storage:

Store locked up
 Store in a well-ventilated place
 Keep cool
 Keep container tightly closed

Disposal:

Dispose of contents/container to hazardous or special waste collection point
 Dispose of contents and containers in accordance with local, regional, national and international regulations

Hazards not otherwise classified (HNOC) or not covered by GHS:

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above recommended exposure limits causes headache, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling.

Other information

Unknown acute toxicity:

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture
Product name(s): MATTE-FIL MATTE URETHANE CLEARCOAT – FAST DRY
Other means of identification: None

CAS number/other identifiers

Chemical / Ingredient Name	CAS No.	Weight %	Synonyms
Tertiary butyl acetate	540-88-5	20 - 30	Not available
Parachlorobenzotrifluoride	98-56-6	5 - 20	Not available
Acetone	67-64-1	3 - 15	Not available
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 7	Not available
Ethyl 3-ethoxypropionate	763-69-9	1 - 7	Not available
Silicon dioxide, chemically prepared	112945-52-5 resp. 7631-86-9	< 4	Not available
2,6-Dimethylheptan-4-one	108-83-8	< 1.5	Not available
Dibutyltin dilaurate	77-58-7	< 0.07	Not available

Any concentration shown as a range above is to protect confidentiality.

This product(s) also contains 40 - 50% of other ingredients which are considered non-hazardous.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****Description of necessary first aid measures****General advice:**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation:

Avoid inhalation of vapor or mist. Remove person to fresh air and keep comfortable for breathing. Keep person warm and at rest. If breathing difficulties persists, seek medical attention. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Eye contact:

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Remove contact lenses, if present and easy to do. Seek medical advice. If eye irritation persists: seek medical attention.

Skin contact:

Take off all contaminated clothing immediately. Wash clothing before reuse. Wash exposed area thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Chemical burns must be treated promptly by a physician. In the case of skin irritation or allergic reactions see a physician.

Ingestion:

If swallowed, seek medical attention immediately and have product container or label at hand. Call a POISON CENTER OR PHYSICIAN. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting unless directed to do so by physician or poison control center. Clean mouth with water and drink afterwards plenty of water. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Keep person warm and at rest. Treat symptomatically. Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed**Potential acute health effects****Eye Contact:**

Causes serious eye irritation.

Inhalation:

May cause respiratory irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Treat as a respiratory sensitizer. May cause shortness of breath, intoxication, headache, nausea, vomiting, respiratory tract irritation. If this product is to be mixed with an isocyanate activator/hardener the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms may include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. May cause headache, dizziness, nausea, vomiting, breathing difficulties, confusion, and unconsciousness. Exposure to high vapor or mist concentrations may cause central nervous system depression. Symptoms of (CNS) depression include dizziness, headache, nausea, fatigue, vomiting and in-coordination.

Skin contact:

Causes skin irritation. Defatting of the skin. May cause skin dryness and irritation. Harmful if absorbed through the skin. May cause an allergic skin reaction. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. Skin contact may cause skin sensitization. In case of skin irritation or allergic reactions see a physician.

Ingestion:

Harmful if swallowed. May result in gastrointestinal distress.

Over-exposure signs and symptoms**Eye Contact:**

Adverse symptoms may include the following:
pain or irritation, watering, redness

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****Inhalation:**

Adverse symptoms may include the following:
respiratory tract irritation, coughing

Skin contact:

Adverse symptoms may include the following:
Irritation, redness, dryness, cracking, blistering may occur

Ingestion:

No specific data

Indication of any immediate medical attention and special treatment needed

No data available on the product. See section 3 and 11 for hazardous ingredients found on the product. Seek professional medical attention for all over-exposures and/or persistent problems.

Note to physicians:

Treatment based on sound judgment of physician and individual reactions of patient. May cause sensitization in susceptible persons. Treat symptomatically. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments:

No specific antidote

Self-protection of the first-aider:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See section 8 for more information.

5. FIRE-FIGHTING MEASURES**Extinguishing media****Suitable extinguishing media:**

Use dry chemical, Carbon dioxide (CO₂), water spray (fog) or alcohol resistant foam

Unsuitable extinguishing media:

Do not use water jet

Specific hazards arising from the substance or mixture:

Highly flammable liquid and vapor. Isolate and restrict area access. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Fight fire from a safe distance and from a protected location. Containers exposed to intense heat from fires should be cooled with water spray to prevent vapor pressure build-up which could result in container rupture. The vapor/gas is heavier than air and will spread along the ground. This product can produce flammable vapors which may travel to a source of ignition and flash back

Hazardous combustion products:

Decomposition products may include the following materials: carbon dioxide, carbon monoxide, halogenated compounds

Special protective actions for fire-fighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from the fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters:

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Dike and collect water used to fight fire. Do not allow run-off from firefighting to enter public sewer systems or public waterways.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****For non-emergency personnel:**

No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not breathe vapor or mist. Eliminate all sources of ignition. Take precautionary measures against static discharges. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Keep people away from and upwind of spill/leak. Beware of vapors accumulating to form explosive concentrations. All equipment used when handling the product must be grounded. See Section 8 for more information.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Avoid release to the environment. Refer to protective measures listed in Sections 7 and 8. See Section 12 for additional Ecological information. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up**Small spill:**

Prevent further leakage or spillage if safe to do so. Do not breathe vapors. Do not touch or walk through spilled material. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Take action to prevent static discharge. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Large spill:

Prevent further leakage or spillage if safe to do so. Ventilate area. Do not breathe vapors. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Approach release from up-wind. Prevent entry into sewers, water courses, basements or confined areas. Do not touch or walk through spilled material. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The contaminated area should be cleaned immediately with a suitable decontaminant. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

If the material contains or is mixed with an isocyanate hardener/activator: Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TM 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance). One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Pressure can be generated. Do not seal waste containers for 48 hours to allow CO₂ to vent. After 48 hours, material may be sealed and disposed of properly. Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see Section 13).

If material does not contain or is not mixed with an isocyanate hardener/activator: Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing.

Special provision:

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. Pressure can be generated. Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities with local regulations.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100**

7. HANDLING AND STORAGE

Precautions for safe handling

Protective measures:

Use appropriate personal protective equipment (see Section 8). Observe label precautions. Handle and open containers with care. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Take precautionary measures against electrostatic discharges. Ground and bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Keep in the original container or an approved alternative made from compatible material, kept tightly closed when not in use. DO NOT handle or store near open flame, heat, or other sources of ignition. DO NOT pressurize, cut, heat, or weld containers. Empty containers may contain hazardous product residues. Keep containers closed when not in use. Protect against physical damage. Do not reuse container. Do not apply to hot surfaces. Sealed containers should be protected against heat as this results in pressure build-up. Follow all SDS/label precautions even after container is emptied because they may retain product residues. Close container after each use. Wash thoroughly after handling. See Section 10 for additional information.

Special precautions:

Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all its parts. DO NOT handle or store near an open flame, heat, or other sources of ignition. Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities:

Keep container tightly closed and sealed until ready for use. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. No smoking. Keep away from heat, sparks, open flames and hot surfaces. Store separately from oxidizing agents and strongly alkaline and strongly acidic materials. Store in accordance with local regulations. Store in a segregated and approved area. Store locked up. Do not store in unlabeled containers. See Section 10 for incompatible materials before handling or use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Protect from temperatures above 45°C/113°F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

Chemical / Ingredient Name	CAS No.	Alberta	British Columbia	Ontario	Quebec	Exposure Limit ACGIH	Immediately Dangerous to Life or Health-IDLH
Tertiary butyl acetate	540-88-5	TWA: 200 ppm TWA: 950 mg/m ³	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m ³	150 ppm STEL 50 ppm TLV-TWA	1500 ppm
Parachloro-benzotrifluoride	98-56-6	Not Available	Not Available	Not Available	Not Available	500 ppm 15 mins. STEL 250 ppm TLV-TWA	Not Available

Version: V01

Preparation Date: June 18, 2020

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY**

SDS No.: 00127

PRODUCT CODE: MC-8100

Continued, Occupational exposure limits:

Chemical / Ingredient Name	CAS No.	Alberta	British Columbia	Ontario	Quebec	Exposure Limit ACGIH	Immediately Dangerous to Life or Health-IDLH
Acetone	67-64-1	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³	500 ppm STEL 250 ppm TLV-TWA	2500 ppm
Solvent naphtha, petroleum, light aromatic	64742-95-6	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
Ethyl 3-ethoxypropionate	763-69-9	Not available	Not available	TWA: 50 ppm TWA: 300 mg/m ³	Not available	Not available	Not available
Silicon dioxide, chemically prepared	112945-52-5	TWA: 10 mg/m ³ Total particulate TWA: 3 mg/m ³ Respirable particles	TWA: 10 mg/m ³ Total dust TWA: 3 mg/m ³ Respirable fraction	TWA: 10 mg/m ³ Inhalable fraction TWA: 3 mg/m ³ Respirable fraction	TWA: 10 mg/m ³ Total dust	TWA: 10 mg/m ³ Inhalable particles TWA: 3 mg/m ³ Respirable particles	Not Available
2,6-Dimethylheptan-4-one	108-83-8	Not Available	Not Available	Not Available	Not Available	25 ppm TLV-TWA	Not Available
Dibutyltin dilaurate *	77-58-7	TWA: 0.2 mg/m ³ , (as Sn) 15 Min.	TWA: 0.1mg/m ³ , (as Sn) STEL: 0.2 mg/m ³ , (as Sn) 15 Min.	TWA: 0.1mg/m ³ , (as Sn)	TWAEV: 0.1 mg/m ³ , (as Sn) STEV: 0.2 mg/m ³ , (as Sn) 15 Min.	0.2 mg/m ³ 15 Mins. 0.1 mg/m ³ TLV-TWA	Not Available

Limits are 8 hours unless otherwise specified

Consult local authorities for provincial or state exposure limits.

Glossary:

- * Absorbed Through Skin
- ACGIH American Conference of Governmental Industrial Hygienists
- Min. Minutes
- OEL Occupational Exposure Limit
- ppm Parts Per Million
- Sn Tin
- STEL Short Term Exposure Limit
- TLV Threshold Limit Value
- TWA Time Weighted Average

Recommended monitoring procedures:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****Appropriate engineering controls****Engineering controls:**

Ensure adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating, lighting and motorized equipment. Use non-sparking tools. Ground and bond container and receiving equipment. Use proper ventilation to remove vapors, mist and fumes combined with NIOSH approved respirator.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Do not let product enter drains.

Individual protection measures**Hygiene measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Wash skin thoroughly with soap and water or use recognized skin cleanser. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Regular cleaning of equipment, work area and clothing recommended. Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes.

Eye/face protection:

Chemical splash goggles. If safety glasses are substituted, include splash guard or side shields. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hand protection:

Appropriate chemical resistant gloves should be worn. Butyl rubber gloves. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc) is noticed. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Skin and body protection:

Skin contact should be prevented through the use of suitable protective clothing, gloves and footwear, selected for conditions of use and exposure potential. Consideration must be given both to durability as well as permeation. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling the product. When there is a risk of ignition from static-electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overall, boots and gloves. Body protection must be chosen based on activity level and exposure.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection:

Do not breathe vapors or mists. Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with clearcoat, during application and until all vapors and spray mists are exhausted. When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards. Full-face supplied-air respirators (SAR) are required in work environments where isocyanate airborne concentrations have not been characterized or are expected to exhibit considerable and sudden variations such as in spray type applications. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Follow respirator manufacturer's directions for respirator use. Respirators must be used according a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Restrictions on use:

Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed to this product if mixed with isocyanate activators/hardeners.

Version: V01
 Preparation Date: June 18, 2020
 SDS No.: 00127

**MATTE-FILMATTE URETHANE
 CLEARCOAT - FAST DRY
 PRODUCT CODE: MC-8100**

General safety and hygiene considerations:

Avoid contact with skin, eyes, or clothing. Always use protective clothing and equipment. Keep food and drink away from material and from area where material is being used. Smoking in area where this material is used is strictly prohibited. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Physical State	Liquid
Color	Opaque Colorless
Odor	Organic solvent
Odor threshold	No data available

Properties

pH (waterborne systems only)	Not applicable
Melting point	No data available
Approximate Boiling point/range	~ 55 °C / 131 °F
Flash point	No data available
Evaporation rate (Air=1)	Slower than Air
Flammability (solid, gas)	No data available
Lower and upper explosive (flammable) limits	Lower: No data available Upper: No data available
Vapor pressure of principal solvent	~41.5 mmHg @ 25°C (Tertiary butyl acetate)
Vapor density (Air = 1)	Heavier than air
Relative density	1.025 - 1.036
Density (kg / gal)	3.88 - 3.92
Density (lbs / gal)	8.55 - 8.64
Solubility	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Percent Weight Water	0
Percent Solids By Weight	43 ± 2
VOC* Less exempt	(g/L) (lbs/gal)
MC-8100 MATTE-FIL Matte Urethane Clearcoat - Fast Dry	154 1.29
VOC, As applied	(g/L) (lbs/gal)
Ready-To-Spray (RTS) with Hardener: H-8101 Hardener with MC-8100 Clearcoat	194 1.62

VOC less exempt (theoretical) and VOC as applied (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. STABILITY AND REACTIVITY

Reactivity:

No data available.

Chemical stability:

Stable under recommended storage and handling conditions. See Section 7 for more information.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****Possibility of hazardous reactions:**

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid:

Avoid all sources of ignition: heat, sparks or open flames. Avoid excessive temperature and direct sunlight. Avoid electrostatic discharge. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Segregate from Incompatible materials.

Incompatible materials:

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products:

Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, isobutylene and acetic acid.

11. TOXICOLOGICAL INFORMATION

This mixture has not been tested for toxicological effects.

Information on likely routes of exposure**Inhalation:**

May cause respiratory irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product is mixed with an isocyanate activator/hardener (see SDS for the hardener), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product. Symptoms can be delayed for several hours.

Eye contact:

Causes serious eye irritation. Moderate pain or irritation, watering, redness and blurred vision. No known significant effects or critical hazards.

Skin contact:

Harmful if absorbed through the skin. Causes skin irritation. May cause an allergic skin reaction. Repeated or prolonged contact may cause defatting and drying of the skin which may result in skin irritation and dermatitis. Skin irritation signs and symptoms may include a burning sensation, redness, swelling and blisters.

Ingestion:

May be harmful if swallowed. Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

Information on toxicological effects**Symptoms related to the physical, chemical and toxicological characteristics:**

Skin contact may aggravate existing skin disease. Prolonged and repeated contact with the skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product. Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema or bronchitis. Prolonged or high exposures may cause CNS effects, liver, adrenal glands and kidney changes. The kidney changes are not likely relevant to humans.

Numerical measures of toxicity**Acute toxicity****Unknown acute toxicity:**

There are no data available on the mixture itself. See Component Information below.

Version: V01
 Preparation Date: June 18, 2020
 SDS No.: 00127

**MATTE-FILMATTE URETHANE
 CLEARCOAT - FAST DRY
 PRODUCT CODE: MC-8100**

Component Information:

Chemical / Ingredient Name	CAS No.	Oral LD50	Dermal LD50	Inhalation LC50
Tertiary butyl acetate	540-88-5	4100 mg/kg (Rat)	>2000 mg/kg (Rabbit)	13300 mg/m ³ (Rat) 4 h
Parachlorobenzotrifluoride	98-56-6	13 g/kg (Rat)	>2.7 g/kg (Rabbit)	33080 mg/m ³ (Rat) 4 h
Acetone	67-64-1	5800 mg/kg (Rat)	>15700 mg/kg (Rabbit)	50100 mg/m ³ (Rat) 8 h
Solvent naphtha, petroleum, light aromatic	64742-95-6	8400 mg/kg (Rat)	>2000 mg/kg (Rabbit)	3400 ppm (Rat) 4 h
Ethyl 3-ethoxypropionate	763-69-9	5 g/kg	>9500 mg/kg (Rabbit)	>5.96 mg/L (Rat) 6 h
Silicon dioxide, chemically prepared	112945-52-5	>5000 mg/kg (Rat)	>5000 mg/kg (Rat)	0.139 mg/L
2,6-Dimethylheptan-4-one	108-83-8	5800 mg/kg (Rat)	16000 mg/kg (Rabbit)	2000 ppm (Rat) 4 h
Dibutyltin dilaurate	77-58-7	2071 mg/kg	Not available	Not available

Conclusion/Summary:
 There are no data available on the mixture itself.

Delayed and immediate effects and also chronic effects from short and long term exposure

Skin corrosion/irritation:
 Causes skin irritation. May cause an allergic skin reaction. Harmful if absorbed through the skin. Prolonged contact may cause severe irritation, with local discomfort or pain, and local redness or swelling.

Serious eye damage/eye irritation:
 Cause eye irritation.

Respiratory or skin sensitization:
 May cause sensitization by inhalation. May cause sensitization by skin contact.

Conclusion/Summary:
 There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness, and in extreme cases loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Skin contact may aggravate existing skin disease. Repeated skin contact may cause dermal irritation, dryness and cracking. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Parachlorobenzotrifluoride may produce allergic skin reaction after prolonged or repeated dermal contact. Acetone has acute oral (rat) and dermal (rabbit) LD50 values of 508 g/kg and 15.7 g/kg respectively. Chronic exposure to vapor may cause dryness of the mouth, headache, dizziness, nausea, and loss of coordination. High concentrations of acetone caused fetotoxic effects in laboratory animal tests.

Germ cell mutagenicity:
 No information available.

Carcinogenicity:
 No information available on the mixture itself.

Version: V01

Preparation Date: June 18, 2020

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100**

SDS No.: 00127

Component Carcinogenicity:

Chemical / Ingredient Name	ACGIH	IARC	NTP	OSHA
Tert-Butyl Acetate	Not Listed	Not Listed	Not Available	Not Available
Parachlorobenzotrifluoride	Not Listed	Not Available	Not Available	Not Available
Acetone	A4	Not Listed	Not Available	Not Available
Solvent naphtha, petroleum, light aromatic	Not Available	Not Available	Not Available	Not Available
Ethyl 3-ethoxypropionate	Not Listed	Not Listed	Not Available	Not Available
Silicon dioxide, chemically prepared	Not Available	3	Not Listed	Not Listed
2,6-Dimethylheptan-4-one	Not Listed	Not Listed	Not Listed	Not Listed
Dibutyltin dilaurate	Not Available	Not Available	Not Available	Not Available

Legend

IARC (International Agency for Research on Cancer)

- Group 3 - Not Classifiable as to Carcinogenicity in Humans
- Group 1 - Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans

ACGIH (American Conference of Governmental Industrial Hygienists)

- A4 - Not Classifiable as a Human Carcinogen

Reproductive toxicity:

There are no data on the mixture itself.

Specific target organ systematic toxicity - repeated exposure:

May cause respiratory irritation. There are no data on the mixture itself.

Target Organs:

Contains material which may cause damage to the following organs:
brain, kidneys, lungs, the nervous system, upper respiratory tract, skin, eye

Aspiration Hazard:

No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

There are no data available on the mixture itself.

Component Ecotoxicity:

Chemical / Ingredient Name	Ecotoxicity - Fresh-water Algae Data	Ecotoxicity - Fish Species Data	Toxicity to microorganisms	Crustacea
Tert-Butyl Acetate	Not Available	296-362 mg/L LC50 (Pimephales promelas) 96 h flow-through	Not Available	Not Available
Parachlorobenzotrifluoride	Not Available	11.5 - 15.8 mg/L LC50 (Lepomis macrochirus) 48 h static EC50: 5.46 - 9.83 mg/L (48 h, Daphnia magna)	Not Available	Not Available

Version: V01
 Preparation Date: June 18, 2020
 SDS No.: 00127

**MATTE-FILMATTE URETHANE
 CLEARCOAT - FAST DRY
 PRODUCT CODE: MC-8100**

Continued, Component Ecotoxicity:

Chemical / Ingredient Name	Ecotoxicity - Fresh-water Algae Data	Ecotoxicity - Fish Species Data	Toxicity to microorganisms	Crustacea
Acetone	Not Available	4.74 - 6.33 mg/L LC50 (Oncorhynchus mykiss) 96 h 6210 - 8120 mg/L LC50 (Pimephales promelas) 96 h static 8300 mg/L LC50 (Lepomis macrochirus) 96 h static	Not Available	EC50: 10294 - 17704 mg/L (48 h, Daphnia magna) EC50: 12600 - 12700 mg/L (48 h, Daphnia magna)
Solvent naphtha, petroleum, light aromatic	Not Available	9.22 mg/L LC50 (Oncorhynchus mykiss) 96 h	Not Available	EC50: 6.14 mg/L (48 h, Daphnia magna)
Ethyl 3-ethoxypropionate	Not Available	62 mg/L LC50 (Pimephales promelas) 96 h static	Not Available	EC50: 970 mg/L (48 h, Daphnia magna)
Silicon dioxide, chemically prepared	Not Available	Not Available	Not Available	Not Available
2,6-Dimethylheptan-4-one	Not Available	Not Available	Not Available	Not Available
Dibutyltin dilaurate	Not Available	Not Available	Not Available	EC50: 0.463 mg/L (48 h, Daphnia magna)

Persistence and degradability

No information available

Bioaccumulation

No information available for the mixture itself. See component information below.

Component Information:

Chemical / Ingredient Name	CAS No.	Partition Coefficient
Tert-Butyl Acetate	540-88-5	1.38
Parachlorobenzotrifluoride	98-56-6	3.72
Acetone	67-64-1	-0.24
Solvent naphtha, petroleum, light aromatic	64742-95-6	Not Available
Ethyl 3-ethoxypropionate	763-69-9	1.35
Silicon dioxide, chemically prepared	112945-52-5	Not Applicable
2,6-Dimethylheptan-4-one	108-83-8	2.56
Dibutyltin dilaurate	77-58-7	Not Available

Mobility in soil:

No information available

Other adverse effects:

No information available

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY**

PRODUCT CODE: MC-8100

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. The generation of waste should be avoided or minimized wherever possible. Do not reuse empty containers. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Waste packaging should not be recycled. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. This material and its container must be disposed of in a safe way. Should not be released into the environment. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with local, regional, national and international regulations.

14. TRANSPORT INFORMATION

Land Transport:	Canada TDG Classification	Land Transport:	U.S. DOT Classification
UN Number:	1263	UN Number:	1263
Proper Shipping Name:	PAINT	Proper Shipping Name:	PAINT
Transport Hazard Class:	3	Transport Hazard Class:	3
Packing Group:	II	Packing Group:	II
Marine Pollutant:	Not available	Marine Pollutant:	Not available
Air Transport:	ICAO/IATA Classification	Ocean Transport:	IMDG Classification
UN Number:	1263	UN Number:	1263
Proper Shipping Name:	PAINT	Proper Shipping Name:	PAINT
Hazard Class:	3	Hazard Class:	3
Packing Group:	II	Packing Group:	II
Marine Pollutant:	Not applicable	Marine Pollutant:	Not available
		Emergency Schedules:	F-E, S-E

For inner packagings not exceeding 5 L each packaged in a strong outer box: Limited Quantity

Additional information:

Special precautions for user:

Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport. Multi-modal shipping descriptions are provided for information purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all the risks deriving from the substances and on all actions in case of emergency situations.

Transport within the user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Proof of Classification statement:

Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Version: V01
 Preparation Date: June 18, 2020
 SDS No.: 00127

**MATTE-FILMATTE URETHANE
 CLEARCOAT - FAST DRY
 PRODUCT CODE: MC-8100**

U.S. Regulatory Rules:

Chemical / Ingredient Name	CAS Number	CERCLA/SARA Section 302	SARA (311, 312) Hazard Class	CERCLA/SARA Section 313
Tertiary butyl acetate	540-88-5	Not Listed	Listed	Not Listed
Parachlorobenzotrifluoride	98-56-6	Not Listed	Not Listed	Not Listed
Acetone	67-64-1	Not Listed	Listed	Not Listed
Solvent naphtha, petroleum, light aromatic	64742-95-6	Not Listed	Not Listed	Not Listed
Ethyl 3-ethoxypropionate	763-69-9	Not Listed	Not Listed	Not Listed
Silicon dioxide, chemically prepared	112945-52-5	Not Listed	Not Listed	Not Listed
2,6-Dimethylheptan-4-one	108-83-8	Not Available	Not Available	Not Listed
Dibutyltin dilaurate	77-58-7	Not Available	Not Available	Not Available

International Inventories

TSCA Status: All components are listed or exempted
DSL/NDSL Status: All components are listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

16. OTHER INFORMATION

Hazardous Material Information System (HMIS):

HMIS Health Rating: Health hazards 3 Flammability 2 Physical hazards 0

National Fire Protection Association (NFPA):

NFPA: Health hazards 3 Flammability 2 Instability 0

Hazard Rating Legend

- * = Chronic Health Hazard
- 0 = Insignificant
- 1 = Slight
- 2 = Moderate
- 3 = High

Note: HMIS® Ratings involve data and interpretations that can vary from company to company. Although HMIS® ratings and the associated label are not required on SDSs, the preparer may choose to provide them. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS must be considered.

The customer is responsible for determining the Personal Protective Equipment (PPE) code for this material. For more information on HMIS® PPE codes, consult the HMIS® Implementation Manual.

Version: V01

Preparation Date: June 18, 2020

SDS No.: 00127

**MATTE-FILMATTE URETHANE
CLEARCOAT - FAST DRY
PRODUCT CODE: MC-8100****Glossary of Terms:**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Services
Ceiling	Maximum Limit Value
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980
CFR	Code of Federal Regulations
EPCRA	Emergency Planning and Community Right-to-Know Act (a.k.a. Title III, SARA)
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
HAP	Listed as a Clean Air Act Hazardous Air Pollutant
HMIS	Hazardous Material Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
NA	Not Available
NFPA	National Fire Protection Association
NIOSH	National Institute of Occupational Safety and Health
NTP	National Toxicology Program
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TPQ	Threshold Planning Quantity
TWA	Time-Weighted Average
UN	United Nations

Prepared By: Regulatory Affairs Department**Preparation Date:** June 18, 2020**Revision Date:** June 18, 2020**Date of Previous Issue:** None**Disclaimer****NOTICE TO READER**

The information contained herein is provided in good faith and believed to be accurate as of the effective date herein. Durafil expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstance be liable for incidental or consequential damages. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Durafil, and to recommend precautionary measures for the storage and handling of the products. However, no warranty, express or implied, is given. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Durafil makes no representations as to its accuracy or sufficiency. The customer/buyer/user is responsible to determine the conditions necessary for the safe use and handling of this product. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, storage and disposal of the product, or from the publication or use of, or reliance upon, the information contained herein. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards, and risks of the product. Durafil cannot guarantee that the hazards described herein are the only hazards that exist. Some or all of the ingredients may present unknown hazards and should be used with caution. It is recommended that each customer/buyer/user or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to understand the data contained herein and the hazards associated with this product. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use.

End of Safety Data Sheet